

Freedom TENS



- Dual channel (4-lead) analog TENS
- Four treatment modes (Normal, Burst, Modulated Rate, Modulated Width)
- Adjustable pulse rate & width
- Treatment timer (15, 30, 60 minutes or continuous)
- Hinged protective cap for intensity dials
- Push button mode & timer selector
- Locking battery & control panel
- Heavy duty metal belt clip
- 1-year warranty



Comes with 1 pkg of 4 reusable self-adhering electrodes, 1 set 43" pin lead wires, 1 each 9V heavy duty battery, carrying case, & instruction manual

Technical Specifications

Channel Dual, isolated between channels

Amplitude Adjustable, 0 - 80mA, Max output 80mA (peak to peak) into 500 ohm load each channel

Output Voltage Adjustable 0 - 40V, Max output 40V (peak to peak) into 500 ohm load each channel

Waveform Asymmetrical biphasic square pulse

Pulse Rate Adjustable, 1 - 150 Hz

Pulse Width Adjustable, 30 - 260 μ S

Modes Four (Burst, Normal, Pulse Width Modulation, Pulse Rate Modulation)

Burst (B) Burst Rate: 2 Hz, Pulse Width: adjustable from 30-260 μ s, Frequency fixed=100 Hz

Normal (N) Pulse Rate: adjustable from 2-150 Hz, Pulse Width: adjustable from 30-260 μ s

Modulated Width (M1) Pulse Width is automatically varied in a cyclic pattern over an interval of 10 seconds, decreasing by 60% of its original value and then increasing back to its original value

Modulation Rate (M2) Pulse Rate is automatically varied in a cyclic pattern over an interval of 10 seconds, decreasing by 40% of its original value and then increasing back to its original value

Timer 15, 30, 60 minutes, or continuous

Power Supply 9 volt battery

Size 10.5 x 6.2 x 3.72 cm

Weight 140 grams including battery

Indications

- Symptomatic relief and management of chronic intractable pain
- Adjunctive treatment for post-surgical and post-traumatic acute pain

Common Uses

- RSD
- Arthritis
- Shoulder syndromes
- Back & cervical muscular/disc syndromes
- Neuropathies

Distributed by

TENS  **Rx**
Your Real Time Healthcare Solution

Phone: 877-372-4441 | Fax: 877-372-5551